

N-Ch 120V Fast Switching MOSFETs

Features

- Split Gate Trench MOSFET technology
- Excellent package for heat dissipation
- High density cell design for low $R_{DS(ON)}$

Product Summary




BVDSS	RDS(on)	ID
120V	2.6mΩ	200A

Applications

- DC-DC Converters
- Power management functions
- Synchronous-rectification applications

TO220AB Pin Configuration



Absolute Maximum Ratings

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	120	V
V_{GS}	Gate-Source Voltage	± 20	V
$I_D @ T_C = 25^\circ C$	Continuous Drain Current, $V_{GS} @ 10V^{1.6}$	200	A
$I_D @ T_C = 100^\circ C$	Continuous Drain Current, $V_{GS} @ 10V^{1.6}$	127	A
I_{DM}	Pulsed Drain Current ²	655	A
EAS	Single Pulse Avalanche Energy ³	1479	mJ
I_{AS}	Avalanche Current	---	A
$P_D @ T_C = 25^\circ C$	Total Power Dissipation ⁴	300	W
T _{STG}	Storage Temperature Range	-55 to 150	°C
T _J	Operating Junction Temperature Range	-55 to 150	°C

Thermal Data

Symbol	Parameter	Typ.	Max.	Unit
$R_{\theta JA}$	Thermal Resistance Junction-Ambient ¹	---	62	°C/W
$R_{\theta JC}$	Thermal Resistance Junction-Case ¹	---	0.42	°C/W

Electrical Characteristics ($T_J=25^\circ\text{C}$, unless otherwise noted)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{\text{GS}}=0\text{V}$, $I_{\text{D}}=250\mu\text{A}$	120	---	---	V
$\Delta \text{BV}_{\text{DSS}}/\Delta T_J$	BV_{DSS} Temperature Coefficient	Reference to 25°C , $I_{\text{D}}=1\text{mA}$	---	---	---	$\text{V}/^\circ\text{C}$
$R_{\text{DS}(\text{ON})}$	Static Drain-Source On-Resistance ²	$V_{\text{GS}}=10\text{V}$, $I_{\text{D}}=84\text{A}$	---	2.6	3.4	$\text{m}\Omega$
		$V_{\text{GS}}=4.5\text{V}$, $I_{\text{D}}=84\text{A}$	---	---	---	
$V_{\text{GS}(\text{th})}$	Gate Threshold Voltage	$V_{\text{GS}}=V_{\text{DS}}$, $I_{\text{D}}=250\mu\text{A}$	2.0	3.0	4.0	V
$\Delta V_{\text{GS}(\text{th})}$	$V_{\text{GS}(\text{th})}$ Temperature Coefficient		---	---	---	$\text{mV}/^\circ\text{C}$
I_{DSS}	Drain-Source Leakage Current	$V_{\text{DS}}=120\text{V}$, $V_{\text{GS}}=0\text{V}$, $T_J=25^\circ\text{C}$	---	---	1	uA
		$V_{\text{DS}}=120\text{V}$, $V_{\text{GS}}=0\text{V}$, $T_J=125^\circ\text{C}$	---	---	100	
I_{GSS}	Gate-Source Leakage Current	$V_{\text{GS}}=\pm 20\text{V}$, $V_{\text{DS}}=0\text{V}$	---	---	± 100	nA
g_{fs}	Forward Transconductance	$V_{\text{DS}}=5\text{V}$, $I_{\text{D}}=84\text{A}$	---	195	---	S
R_g	Gate Resistance	$V_{\text{DS}}=0\text{V}$, $V_{\text{GS}}=0\text{V}$, $f=1\text{MHz}$	---	2.7	---	Ω
Q_g	Total Gate Charge	$V_{\text{DS}}=60\text{V}$, $V_{\text{GS}}=10\text{V}$, $I_{\text{D}}=84\text{A}$	---	146.9	---	nC
Q_{gs}	Gate-Source Charge		---	57.7	---	
Q_{gd}	Gate-Drain Charge		---	32.3	---	
$T_{\text{d(on)}}$	Turn-On Delay Time	$V_{\text{DD}}=60\text{V}$, $R_{\text{G_ext}}=2.7\Omega$, $V_{\text{GS}}=10\text{V}$	---	32.7	---	ns
T_r	Rise Time		---	80.3	---	
$T_{\text{d(off)}}$	Turn-Off Delay Time		---	78.7	---	
T_f	Fall Time		---	47.3	---	
C_{iss}	Input Capacitance	$V_{\text{DS}}=60\text{V}$, $V_{\text{GS}}=0\text{V}$, $f=1\text{MHz}$	---	9560	---	pF
C_{oss}	Output Capacitance		---	1220	---	
C_{rss}	Reverse Transfer Capacitance		---	42	---	

Diode Characteristics

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I_s	Continuous Source Current ^{1,4}	$V_G=V_D=0\text{V}$, Force Current	---	---	200	A
V_{SD}	Diode Forward Voltage ²	$V_{\text{GS}}=0\text{V}$, $I_s=84\text{A}$, $T_J=25^\circ\text{C}$	---	---	1.4	V
t_{rr}	Reverse Recovery Time	$I_F=84\text{A}$, $dI/dt=100\text{A}/\mu\text{s}$, $T_J=25^\circ\text{C}$	---	90.2	---	nS
			---	239.9	---	nC

N-Ch 120V Fast Switching MOSFETs

Typical Performance Characteristics

Fig 1: Output Characteristics




Fig 2: Transfer Characteristics




Fig 3: Rds(on) vs Drain Current and Gate Voltage




Fig 4: Rds(on) vs. Gate Voltage




Fig 5: Rds(on) vs. Temperature





Fig 6: Vgs(th) vs. Temperature



N-Ch 120V Fast Switching MOSFETs


Fig 7: BV_{dss} vs. Temperature

Fig 8: Capacitance Characteristics




Fig 9: Gate Charge Characteristics




Fig 10: Body-diode Forward Characteristics




Fig 11: Power Dissipation





Fig 12: Drain Current Derating



N-Ch 120V Fast Switching MOSFETs

Fig 13: Safe Operating Area





Fig 14: Max. Transient Thermal Impedance



Test Circuit

N-Ch 120V Fast Switching MOSFETs




Figure A. Gate Charge Test Circuit & Waveforms




Figure B. Switching Test Circuit & Waveforms





Figure C. Unclamped Inductive Switching Circuit & Waveforms

Mechanical Dimensions for TO-220



COMMON DIMENSIONS

SYMBOL	MM	
	MIN	MAX
A	9.70	10.30
B	3.40	3.80
C	8.80	9.40
D	1.17	1.47
E	2.60	3.50
F	15.10	16.70
G	19.55MAX	
H	2.54REF	
I	0.70	0.95
J	9.35	11.00
K	4.30	4.77
L	1.20	1.45
M	0.40	0.65
N	2.20	2.60